

Ingenico 2600

Check reader and imager

TECHNICAL CHARACTERISTICS

- The Ingenico 2600 is powered by a 32 bit, 24 MHz processor that provides fast check imaging and transaction finalization
- Its check and document imager provides comfort in the knowledge that NSF, administrative returns or disputed checks have been imaged, stored, and are ready for retrieval by the merchant, customer, collection agency or other authorized provider
- The 2600's MICR reader allows merchants to leverage existing services for verification or guarantee, while leveraging the benefits of electronic check conversion
- The optional magnetic stripe reader allows a merchant to use one device for check verification, guarantee and conversion, reducing equipment cost while increasing transaction security and customer checkout throughput
- The Ingenico 2600 provides an optional fixed function ink jet printer, for printing limited text messages such as "ACH Processed" or "Electronically Processed" on the check face, reducing operator confusion and eliminating the need to stamp the check or print on an ECR
- Included are multiple connectivity selections for dial EFT-POS terminals, PC and electronic cash registers. The unit even provides an optional modem for stand-alone EFT-POS terminal operations
- The Ingenico 2600 is a versatile device that can be powered by the host device or an external source
- The Ingenico 2600 provides eⁿ-Check 2500 emulation for EFT-POS terminal, PC or ECR connectivity; or RDM emulation for connectivity, operations and data formatting

Ingenico 2600

Processor	32-bit 24 MHz processor
Memory	512 Kb Flash Memory for operating system 1 MB or 2 MB, Flash for image storage 2 MB DRAM for OS use, image capture and processing
Communication Ports and Options	(2) RS232 ports RS485 port for IBM Tailgate (Feature C emulation) Optional USB connection Optional 33.6 Kbps modem for stand-alone operations
MICR Reader Images	E13B and CMC7 auto-sense Images captured at 200 dpi, 256 Grey Scale Standard output is TIFF format with Group 4 compression converted to black and white Average personal check image is under 10 Kb
Magnetic Stripe Reader Option	Bi-directional reader Track 1 & 2 Track 1, 2, & 3
Void Printer Option	Fixed Printer for printing "ACH Processed", "Electronically Processed" or other limited messages on the face of the check (2) available font sizes Ink Jet Cartridge available in red, black or blue ink Text message is programmable
User Interface	3-color (amber, red, & green) LED status indicator
Application Software	Applications are written in ANSI standard C and are pre-loaded
Power	0.5 amps @ 12VDC No power supply is required in most installations when at least 300 mA is available from POS port
Dimensions & Weight	5.2" (132 mm) x 6.5" (165 mm) x 5.2" (132 mm) 2.06 lbs (938 grams)

Ingenico Inc.

1003 Mansell Road - Atlanta, GA 30076
Tel: (770) 594-6000 - Fax: (770) 594-6003
www.ingenico-us.com

Ingenico Canada Ltd.

79 Torbarrie Road - Toronto, Ontario
Canada M3L 1G5
Tel: (416) 245-6700 - Fax: (416) 245-6701
www.ingenico-ca.com